

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

International Radiation Detectors Inc.

SXUV Series Photodiodes

SXUV Series

Silicon p-n junction photodiodes with platinum silicide front entrance windows have been developed by International Radiation Detectors for detection of XUV photons (energy range 4 eV to 12 keV). These devices have been specifically developed for photon detection with high flux levels like those encountered in the third and the fourth generation synchrotrons and the excimer lasers. The SXUV series diodes are fabricated by an ULSI (Ultra Large Scale Integrated Circuit) compatible process and their construction is shown in the following figure.




Fig. 1: Cross - Section of the SXUV Photodiodes

Developed in collaboration with NIST, NIH

[Return to Main Page](#)



Delivering Unparalleled Performance